

4 4891-19

4/13/2015

1/4



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

April 13, 2015

Kevin R. Kutcel  
Agent for New Nautical Coatings, Inc.  
New Nautical Coatings, Inc.  
14805 49<sup>th</sup> Street  
Clearwater, FL 33762

Subject: Notification per PRN 98-10 – Optional Marketing Statements  
Product Name: Sea Hawk Smart Solution  
EPA Registration Number: 44891-19  
Application Date: March 27, 2015  
Decision Number: 503109

Dear Mr. Kutcel:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped "Notification" and will be placed in our records.

If you have any questions, you may contact Terria Northern at 703-347-0265 or via email at [northern.terria@epa.gov](mailto:northern.terria@epa.gov).

Sincerely,

A handwritten signature in black ink, appearing to read "John Hebert", written over a horizontal line.

for

John Hebert, Branch Chief  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

# Sea Hawk

PREMIUM QUALITY

# SMART SOLUTION

Antifouling Coating

### NOTIFICATION

44891-19

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

04/13/2015

### OPTIONAL MARKETING STATEMENTS

- (OUTDRIVE PAINT)
- (Metal Free Coating)
- (Outboard Paint)
- (Lower Unit Coating)
- (Barnacle Protection)
- (Environmental Buoy Paint)
- (Eco Buoy)
- (Crap Trap Paint)

**KEEP OUT OF REACH OF CHILDREN**

**DANGER**

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

Active Ingredients:	
(2-(p-chlorophenyl)-3-cyano-4-bromo-5-trifluoromethyl pyrrole)(tralopyril)	2.90%
Other Ingredients:	<u>97.10%</u>
TOTAL	100.00%

\*Contains petroleum distillates, xylene, or xylene range aromatic solvents.

LIMITED WARRANTY: The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.

**Net Contents 1 PINT**

**U.S. Measure**

**.4732 Liters**

**NEW NAUTICAL COATINGS, INC.**

14805 49th Street North  
Clearwater, FL 33762  
[www.seahawkpaints.com](http://www.seahawkpaints.com)

**DIRECTIONS FOR USE:** It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.  
**GENERAL DESCRIPTION:** Ablative, self-polishing antifoulant. This product is designed to control barnacles, algae and other marine fouling in salt or fresh water. This product is designed for use on the surfaces of hulls on ships, boats, barges, yachts, or running gear.

Shake vigorously for several minutes with a mechanical paint shaker before use. Due to the settlement in the product, if this product is not properly shaken it will become ineffective.

**SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION**

**PRODUCT INFORMATION**

**Finish/Sheen:** Semi-Glöss  
**Converter:** One Pack  
**Volume Solids:** 50% ± 2%  
**Mix Ratio:** One Pack  
**Shipping Weight:** 12-13 lbs/gal  
**Flash Point:** 100° F/38° C  
**Film Thickness:** 6 mils wet equals 2.7 dry per coat  
**Recommended Coats:** 3  
**Theoretical Coverage:** 267 sq.ft./gal. @ recommended film thickness.

**APPLICATION DETAILS**

**Sweat-In Time:** N/A  
**Thinner:** Sea Hawk 2033, 2035  
**Cleaner:** Sea Hawk Xylene 7130

**OVERCOATING INTERVALS:**

**Drying Time (Hrs):**

Substrate Temp.	Touch	Min.	Max.	Launch
73°F (23°C)	2 Hrs	1 Hr	N/A	12 Hrs
95°F (35°C)	1 Hr	1 Hr	N/A	12 Hrs

**Consult your Sea Hawk Representative for the system best suited for surfaces to be protected.**

**REGULATORY DATA**

**VOC:** 298 Grams/Liter

**Limitations:** Apply in good weather when air and surface temperature are above 50° F (10°C). Surface temperatures must be at least 50°F (10°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40-100°F (4-38°C). Prolonged atmospheric exposure of the product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating application procedures. See published data sheets for more specific application data. As application, environment and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of coating.

**SURFACE PREPARATION:** Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing (SSPC-SPI).

**Application:** This product can be applied by brush, roller, or spray.

**Thinning:** We do not recommend thinning. If necessary, thin no more than 10% by volume with 2033 or 2035.

**Clean Up:** Clean all equipment immediately after using with Sea Hawk Xylene 7130.

**Safety:** Read and observe all precautionary statements on this Label.

**STORAGE AND DISPOSAL**

Do not contaminate food, feed or water by storage or disposal. **Storage:** Do not store near open heat or flame. Store in well ventilated area.

**Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**Container Disposal:** Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**DANGER. Corrosive:** Causes irreversible eye damage. Causes skin irritation. May be fatal if swallowed. Harmful if inhaled. Do not get in eyes or clothing. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Avoid contact with skin, eyes or clothing. Avoid breathing vapor or spray. When handling, wear goggles or face shield, chemically resistant gloves, long sleeved shirt and pants, socks, chemical resistant footwear, and chemically resistant gloves (such as Barrier Laminate, Butyl Rubber, and Nitrile Rubber). When mixing, loading, or cleaning equipment, wear chemical-resistant apron. For overhead exposure wear chemical-resistant headgear. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco. Remove and wash contaminated clothing before reuse.

**ENVIRONMENTAL HAZARDS**

This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact you State Water Board or Regional Office of the EPA.

**PHYSICAL AND CHEMICAL HAZARDS**

Combustible. Do not use or store near open flame.

<b>First-Aid</b>	
If in eyes:	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes. then continue rinsing. Call poison control center or doctor for treatment advice.
If on skin:	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
If swallowed:	Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to by a poison control center or doctor. Do not give anything to an unconscious person.
If inhaled:	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for treatment advice.
<b>NOTE TO PHYSICIAN:</b>	May pose an aspiration pneumonia hazard. Contains petroleum distillate.
Have the product container or label with you when calling a poison control center or doctor or going for treatment. For emergency information or {product, use, etc.}, call a National Pesticides Information Center at 1-800-858-7378, 6:30AM to 4:30PM Pacific Time (PT), seven days a week. During other times, call poison control center 1-800-222-1222.	